

# PRODUCT DATA

## SINGLE PACK ETCH PRIMER



### Type

A Single Pack Polyvinyl Butyric-Based Primer containing Alcohol and Aromatic Hydrocarbons.

### Appearance

Dries to a Light Sheen finish.

### Properties and Uses

Used as a key coat to ensure good adhesion to well prepared Aluminium, Galvanised Steel, Mild Steel and various alloys. Could also be used as a finish coat.

### Surface Preparation

Essential for good paint performance is a sound substrate that has been properly cleaned and prepared. All surfaces must be dry and grease-free prior to applying Etch Primer.

### New Metal Surfaces

Degrease by applying Titanium Ti-Clean. Leave on the surface for 15 minutes. Rinse off with clean water and allow to dry.

1<sup>st</sup> coat: Titanium Single Pack Etch Primer

2<sup>nd</sup> coat: Titanium Single Pack Etch Primer

<b><u>Application Method:</u></b>	Brush or conventional spray.
<b><u>Spreading Rate:</u></b>	± 5m <sup>2</sup> per litre per coat on smooth surfaces.
<b><u>Cleaning of Utensils:</u></b>	Etch Primer Thinners.
<b><u>Packaging Sizes:</u></b>	5 L and 1 L
<b><u>Colour Range:</u></b>	Black and Red Oxide.
<b><u>Drying Time:</u></b>	Touch dry : 5 minutes Re-coating time : 30 minutes