

PRODUCT DATA

TI-COVER



Type

Good quality Alkali-Resistant Waterbased Paint.

Appearance

Smooth Matt Finish.

Properties and Uses

Ti-Cover has a high opacity and is suitable for use on Creststone ceilings, one coat plaster and fibre cement surfaces.

Surface Preparation

Essential for good paint performance is a sound substrate that has been properly cleaned and prepared. On existing painted surfaces to be redecorated, a small section of paint must be removed to establish the condition of the original paint and the substrate. Where there is doubt, the paint must be removed to a sound base. All surfaces must be dry, free from loose and flaky material, grease and fungus prior to applying the new paint system.

Application Instructions

These instructions are issued as an aid in determining correct surface preparation, mixing and application procedure and should be closely followed to obtain maximum service from the material.

1. New Unpainted Crete Stone Ceiling Surfaces

(a) 1st and 2nd coat: Titanium White Ti-Cover

2. Painted Ceilings

(a) 1st and 2nd coat: Titanium White Ti-Cover

3. Unpainted Off-Shutter Concrete Ceilings

(a) Fill all pin holes with Titanium Ti-Fill.

(b) 1st coat: Titanium White Ti-Nyl Masonary Paint.

(c) 2nd and 3rd coat: Titanium White Ti-Cover

Application Method: Brush, roller or airless spray.

Spreading Rate: ± 6m² per litre per coat on very smooth surfaces.

Cleaning of Utensils: Wash immediately after use with warm soapy water.

Hardened splashes can be removed with Meths.

Packaging Sizes: 20 L, 5 L and 1 L

Colour Range: White. Pastels on request.