

PRODUCT DATA

WHITE WOOD PRIMER



Type

A Mineral Turpentine Soluble Coating based on a blend of Alkyd Resin and Vegetable Oils.

Appearance

Titanium White Wood Primer dries to an Eggshell finish.

Properties and Uses

Titanium White Wood Primer is suitable for the priming of all suitably prepared soft woods, both internally and externally.

Surface Preparation

Essential for good paint performance is a sound substrate that has been properly cleaned and prepared. On existing painted surfaces it is recommended that a small section of paint be removed to establish the condition of the original paint and the substrate. Where there is doubt, the paint must be removed to a sound base. All surfaces must be dry, free from loose and flaky material, grease and fungus prior to applying the new paint system.

Application Instructions

These instructions are issued as an aid in determining correct surface preparation, mixing and application procedure and should be closely followed to obtain maximum service from the material.

- (a) Titanium White Wood Primer should only be used on bare wood and not over existing paints.
- (b) It is important to allow a minimum of 24 hours drying time before over-coating.

<u>Application Method:</u>	Brush.
<u>Spreading Rate:</u>	± 8m ² per litre.
<u>Drying Time:</u>	Surface dry 6 hours and hard dry 24 hours at 25°C.
<u>Cleaning of Utensils:</u>	Mineral Turpentine.
<u>Packaging Sizes:</u>	5 L and 1 L
<u>Colour Range:</u>	White only.